

MAGNETIC PAINT

Excellent magnetic coating.

SPECIAL FEATURES

High quality interior water paint applied directly on acrylic painted walls.

SUGGESTED USES

Recommended for children rooms, kitchens, restaurants and schools.

TECHNICAL DATA

Product code:	797-300
Color:	Grey- can be recoated with acrylic paint
Gloss:	Matt
Calculated spreading rate*:	2-3 sq.m/liter (in 3 coats)
Recommended Thinner:	Ready for use
Drying Times:	Touch dry**: 30 minutes; Hard coat: 24 hours; Dry to recoat: 30 minutes
Shelf life:	24 months
Quantity per Pallet:	Package size: 0.908 liter

SURFACE PREPARATION AND PAINT SYSTEM

Ensure surfaces to be painted are in sound condition, thoroughly sanded to a smooth finish, dry, free from dirt, dust, and loose material.

Magnetic paint has to be painted on acrylic paint. Can be painted directly on wood or plaster walls.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.