

Acrylic45.

Water Based Acrylic Paint Especially Suited for Exterior Walls.

SPECIAL FEATURES

Breathing, environment friendly, lead and chromates free.

SUGGESTED USES

Painting exterior plastered walls, concrete and bricks walls.

TECHNICAL DATA

Product code:	700-401 white, 700-402 P based,	
Color:	White and Base P	
Gloss:	Matt	
Calculated spreading rate*:	6 sq.m/liter (in two coats)	
Recommended Thinner:	During application: water. For cleaning: water and soap.	
Drying Times:	Touch dry**: 1 hour. Hard coat: 3 Days Dry to recoat: 2-3 hours	
Shelf life:	24 months	
Quantity per Pallet:	Package size	Quantity per Pallet
	18 liters	27

SURFACE PREPARATION AND PAINT SYSTEM

Concrete and Cement Exterior Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust and apply a first coat of **Tambourflex Primer White** diluted by about 30% mineral white spirit (applied by brush, roller or spray). Allow to dry for 24 hours at least and apply 2 coats of **Acrylic45**

Painted Walls

Remove any old, loose and peeling paint. Use **Tambourflex Filler Putty** to smooth and fill holes. Allow to dry and sand with sandpaper to obtain a smooth surface. Fill any structural cracks with **Tambourflex Filler Putty**. Apply 2 coats of **Acrylic45**, diluted as required.

APPLICATION REMARKS

Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless: Dilute the paint with water for the first coat by 20% - 30%. Dilute the paint with water for the additional coats by 10%-20%.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.