

SUPERCRYL SATIN FINISH

Unique, Acrylic, Water Based Paint for Providing a Special Satin Finish to Walls and Wood

SPECIAL FEATURES

Elegant finish easily washed and cleaned, fast drying, lead and chromates free.

SUGGESTED USES

Painting interior and exterior plastered, concrete, bricks and wooden walls.

TECHNICAL DATA

Product code:	713-101/713-102/713-103/713-104/713-105 (White+4 Tinting Bases)	
Color:	1200 shades from the Spectrum fan deck	
Gloss:	Semi gloss	
Calculated spreading rate*:	8-9 sq.m/liter (in two coats)	
Recommended Thinner:	During application: Water.	
For cleaning:	Water and soap. When dry: Water and soap.	
Drying Times:	Touch dry**: 1 Hour Hard coat: 24 hours Dry to recoat: 2-3 hours	
Completely dry for cleaning and washing:	7 days after application.	
Shelf life:	24 months	
Quantity per Pallet:	Package size	Quantity per Pallet
	5 liters	80 ea
	18 liters	27 ea

SURFACE PREPARATION AND PAINT SYSTEM

Surface must be clean of dust and any other foreign material. Stir well before application.

Interior Whitewashed surfaces

Remove any flakey, loose or peeling lime and excessively thick coats. Sand with sandpaper until a smooth surface is obtained. Clean dust thoroughly. Apply one coat of **Bonderol Super Primer** and allow to dry for 4 hours. Apply two coats of **Supercryl Satin Finish** where the first coat is diluted with water by 20%-30%. Allow to dry for 3 hours and apply a second coat, diluted with water by 15%-25%.

Painted Interior Walls

Remove any flakey, loose or peeling old paint. Apply a coat of **Bonderol Super Primer** on peeling paint sections. Apply two coats of **Supercryl Satin Finish** where the first coat is diluted with water by 20%-30%. Allow to dry for 3 hours and apply a second coat, diluted with water by 15%-25%. When the old paint is intact and cannot be removed, apply 2 coats of **Supercryl Satin Finish** directly on that paint, according to the above procedure.

New Interior Cement Plastered Walls

Smooth the surface lightly with sandpaper. Remove dust and plaster spray. Fill holes with **Calcimo X**. Apply 1-2 coats of **Tambourfill** diluted with water by 5%- 10% and allow to dry for 4 hours. Apply two coats of **Supercryl Satin Finish** where the first coat is diluted with water by 20%-30%. Allow to dry for 3 hours and apply a second coat, diluted with water by 15%-25%.

Concrete and Cement Plastered Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust, and apply 1 coat of **Tambourflex Primer** diluted with 30% mineral spirit and two coats of **Supercryl Satin Finish** where the first coat is diluted with water by 20%-30%. Allow to dry for 3 hours and apply a second coat, diluted with water by 15%-25%.

- In each of the above cases, use **Glue Putty 2000** to smooth the wall prior to applying **Supercryl Satin Finish** . Apply one **Supercryl Satin Finish** coat diluted by 40% water and then apply two coats of **Supercryl Satin Finish** where the first coat is diluted with water by 20%- 30%. Allow to dry for 3 hours and apply a second coat, diluted with water by 15%-25%.
- It is recommended to use a short bristled roller, intended for semi-glossy paints.

Building Joinery and Wooden Doors

Apply one coat of **Wood and Wall Oil Sealer** thinned with White Spirit by 40%-50%. Apply two coats of **Glue Putty 2000** (for interiors) or **PVA Putty**, (for exteriors). Allow to dry and polish to obtain a smooth surface. Apply 1-2 coats of **Synthetic Wood Primer**. Allow to dry for 24 hours between coats. Polish the surface, clean off dust and apply 2 coats of **Supercryl Satin Finish**.

Unpainted Wood

Prepare the wooden surfaces by sanding with sandpaper. Fill holes and grooves with **PVA Putty**. Allow to dry and polish to obtain a smooth surface. Apply 1-2 coats of **Synthetic Wood Primer**. Allow to dry for 24 hours between coats. Polish the surface, clean off dust and apply 2 coats of **Supercryl Satin Finish**.

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.