

# ACRYNOL for BATHROOM & KITCHEN

Premium Quality, Water Based Acrylic Paint for Anti Fungus and Mould-Resistant

## SPECIAL FEATURES

Protects against fungus and mould resistant. Odor free. Washable, lead and chromates free.

## SUGGESTED USES

Painting interior walls or concrete and ceilings in rooms already contaminated or likely to be contaminated by mould, rather frequently (bathrooms, kitchen, living rooms, etc.). Also suitable for painting concrete surfaces, asbestos cement plaster, wood and surfaces painted with water diluted paints.

## TECHNICAL DATA

Product code: 724-001 white, 724-002 P based.  
 Color: White, and 400 colors from Tambour Spectrum fendeck  
 Gloss: Matt  
 Calculated spreading rate\*: 5-6 sq.m/liter (in two coats)  
 Recommended Thinner: **During application:** water. **For cleaning:** water and soap.  
 Drying Times: **Touch dry\*\*:** 3 hours. **Hard coat (7 days) Dry to recoat:** 24 hours  
 Shelf life: 24 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
1 liter	576
5 liters	80

## SURFACE PREPARATION AND PAINT SYSTEM

### Internal moldy surfaces

**Acrynol for Bathroom and Kitchen** prevents mould and fungi development on clean surfaces, but it does not destroy existing mould and fungi. Therefore, if the surface you intend to paint is already contaminated, clean it thoroughly before painting. Clean by rinsing the surface with **Fungicheck** solution, diluted with water (see application instructions of the **Fungicheck** solution). Start painting only after the surface has been thoroughly rinsed with water and dried. Once the surface is prepared, apply the paint according to the application instructions for clear surfaces.

### Internal surfaces, Unaffected by Mold

#### Cement, Plaster or Asbestos-Cement

Stir the paint well. Repair defects using **PVA Putty**, when needed. Apply a first coat of **Acrynol**, diluted by 20% water and allow drying. Apply two additional coats of **Acrynol**, diluted by 5%-15% water.

#### Whitewashed Surfaces

Remove any loose, flakey, peeling lime or excessively thick layers. Repair defects using **PVA Putty**. Apply one coat of **Bonderol Super Primer** diluted with water and allow to dry. Apply two additional coats of **Acrynol**.

## APPLICATION REMARKS

Stir the paint well before application and while painting.

**Roller Application:** Dip the roller in paint and then remove excess paint (in the oval, 5 liters container, you can dip the roller directly in the container). Apply a thick and generous coat. To obtain a nice and uniform finish, cover the entire wall and then finish by light crisscross rolling.

**Brush/ Pad application:** Dilute up to 15% with water and stir well.

## CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

## CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

## GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

\* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

\*\* at 25°C and 65% relative humidity.