

Your Imagination...Our Paint.

SUPERCRYL 2000 FREE

"Green", User and Environment Friendly, Odorless Acrylic Paint

SPECIAL FEATURES:

Excellent and unique acrylic paint combining user and environment protection properties with high product quality.

With very low VOC (organic hydrocarbon emission) properties, odor free Green SUPERCRYL is the ideal choice for users who are sensitive to odors during and after the application. Green SUPERCRYL may be applied in populated spaces without removing the occupants, e.g., hospitals, children rooms, etc.

SUPERCRYL 2000 provides high coverage rate, in bright white, without any brush marks, that lends a very elegant look to the wall.

Awarded the green label by the Standards Institute.

SUGGESTED USES:

For interior application.

TECHNICAL DATA:

Product Code: 728-101 white, 728-102 pastel base, 728-103 median base, 728-104 deep base, 728-105 transparent base.

Color: White, 1200 shades of the spectrum chart and any shade of the other charts in the market.

Gloss: Matt-satin.

Calculated spreading rate*: 6-7 sq.m/liter (in two coat)

Recommended Thinner: During Application: water **Cleaning:** water and soap.

Drying Times: Touch dry:** 1 hour; **Hard Coat:** 3 hours. **Dry to recoat:** 2-3 hours

Drying for cleaning and washing the wall: 7 days

Shelf life: 24 months

Quantity per Pallet:	Package size	Quantity per Pallet
	18 Liters	36
	15 Liters	27
	10 Liters	44
	5 Liters	80
	3 Liters	210
	1 Liter	576

SURFACE PREPARATION AND PAINT SYSTEM:

Interior whitewashed surfaces:

Remove any free, loose, peeling white wash or very thick coats. Use sandpaper to obtain a smooth surface. Clean the dust thoroughly. Apply one coat of BONDROL SUPER and allow to dry for 4 hours. Apply two coats of SUPERCRYL 2000 Green in an elegant look, diluted with 5% - 10% water.

Your Imagination...Our Paint.

Interior walls painted with plastic paint:

Remove any old, loose, peeling paint. Apply one coat of BONDROL SUPER on peeled paint areas. Smooth the surface using MAGIC BOND SUPER or PUTTY ADHESIVE 2000 (for interior application only) and apply one coat of BONDROL SUPER. Apply 2-3 coats of SUPERCRYL 2000 Green in an elegant look

New unpainted interior walls (finishing plaster):

Use sandpaper to smooth the surface lightly. Remove the dust and fill holes with CALCIMO X or with CALCIMO FINE. Apply 1-2 coats of TAMOURFILL diluted with 5% - 10% water and allow to dry for 4 hours. Apply the first coat of SUPERCRYL 2000 Green in an elegant look, diluted with 5% - 10% water and apply a second and third coat of SUPERCRYL 2000 Green in an elegant look, diluted with 5% - 10% water, as needed.

PAINT APPLICATION:

Mix the paint thoroughly before application and during application,

Roller Application:

Dilute with 5% - 10% water and mix thoroughly. Dip the roller in the paint and remove excess paint (in the 5 liters oval container, you can dip the roller directly in the container). Apply 2-3 coats according to the surface type. Apply until the surface is completely covered and then roll lightly in crisscross movements to obtain an elegant, uniform look.

Brush/ Pad Application:

Pour the paint into another container. Dilute with 5% - 10% water and mix thoroughly. Apply 2-3 coats according to the surface type.

Please note: in shades based on A and D bases, apply one coat of primer for interior walls, red or yellow (according to the applied shade), specifically suited for use as a primer for top acrylic paints. Application of one coat of primer for interior walls ensures maximum coverage and exact shade of the top coat. Then apply SUPERCRYL 2000 Green in an elegant look according to the instructions.

TOOLS CLEANING AND STORAGE:

Clean the tools with water and soap immediately upon completing the application. Pour a thin layer of water on the remaining paint and close the container tightly, to prevent air penetration. Store in a roofed, ventilated place.

CAUTION:

Inedible. The product is not defined as a hazardous material and does not contain materials that require special marking or warning. Keep away from children. Provide adequate ventilation of the work space. Read the applicable information on the product in the Safety Data Sheet (MSDS).

GENERAL COMMENTS:

Do not apply the paint when rain is expected and/or when walls temperature falls below 10 degrees Celsius and relative humidity exceeds 85%. Do not mix this product with products that are not recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

Your Imagination...Our Paint.

* Practical spreading rate depends on several factors: The surface, the application mode, color shades, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** At 25°C and 65% relative humidity.

IS 1945 + scrubbing table, green label, 7 years warranty.

Produced by Tambour, authorized by the Israeli Institute of Standards, complying with ISO 9001.