

# Supercryl Antibacterial

An acrylic wall paint for a cleaner, safer and more hygienic environment

## SPECIAL FEATURES

An innovative paint developed in collaboration with UK based BioCote Ltd which incorporates an antibacterial silver additive. Ensures sustainable protection against build-up of bacteria and mould on the wall surface. Helps reduce the risk of potential infections caused by environmental contamination for the life of the paint.

## SUGGESTED USES

For internal painting of various kinds of walls in Health institutions, old-age homes, food factories, restaurants, schools, leisure centers and additional public places where hygiene is important. Also recommended for use in humid and hot places such as bath rooms and toilets to help stop the build-up of black mould which is difficult to remove and affects the décor of the room.

## TECHNICAL DATA

Product code: 732-801 white, 732-802 P based.  
 Color: White, and 400 colors from Tambour Spectrum fendeck  
 Gloss: Matt  
 Calculated spreading rate\*: 6-7 sq.m/liter (in two coats)  
 Recommended Thinner: **During application:** water. **For cleaning:** water and soap.  
 Drying Times: **Touch dry\*\*:** 3 hours. **Hard coat (7 days)** **Dry to recoat:** 24 hours  
 Shelf life: 24 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
1 liter	576
5 liters	80
10 liters	36
15 liters	36
18 liters	36

## SURFACE PREPARATION AND PAINT SYSTEM

### Interior Whitewashed Lime surfaces

Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Apply one coat of **Bonderol Super**. Allow to dry for 4 hours and apply two coats of **Supercryl Antibacterial**.

### Painted Interior Walls

Remove any old, loose and peeling paint. Apply a coat of **Bonderol Super** on peeling paint surfaces. Smooth the surface by applying **Magic Bond** or **Glue Putty 2000** (for interior applications only), apply a coat of **Bonderol Super** over it and allow to dry. Apply 2-3 coats of **Supercryl Antibacterial**. When the old paint coat is whole and cannot be removed, apply 2-3 coats of **Supercryl Antibacterial** directly on it.

### New, Unpainted, Plastered Interior Walls

Smooth the surface lightly using sandpaper. Remove dust and fill holes with **Calcimo X**. To obtain a smooth surface, apply a coat of **Tambourfill** and allow drying for 4 hours. Apply 2-3 coats of **Supercryl Antibacterial**.

### Concrete and Cement Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust and apply a first coat of white **Bonding Primer White** diluted by about 30% with Tambour Mineral white spirit. Allow to dry for 24 hours at least. Apply 2-3 coats of **Supercryl Clean...**

## APPLICATION REMARKS

Stir the paint well before application and while painting.

**Roller Application:** Dip the roller in paint and then remove excess paint (in the oval, 5 liters container, you can dip the roller directly in the container). Apply a thick and generous coat. To obtain a nice and uniform finish, cover the entire wall and then finish by light crisscross rolling.

**Brush/ Pad application:** Dilute up to 15% with water and stir well.

## CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

## CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

## GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

\* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

\*\* at 25°C and 65% relative humidity.