

Polisid

A water based emulsion type paint, designed to replace the traditional whitewash inside ceiling and walls applications.

SPECIAL FEATURES

Uniform and smooth finish, do not erode, economic.

SUGGESTED USES

For internal walls and ceilings.

TECHNICAL DATA

Product Code:	731-700		
Colour:	White		
Based on:	Synthetic Resins		
Package Size:	18 litre		
Gloss:	Matt		
Calculated spreading rate [max]:	6.0 m ²		
Touch Dry [max]:	1 hour	Recoat: 2 hours	Hard Dry; Hours 3 hours
Thinner:	Water		
Cleaning Thinner:	Soap and Water		
Shelf life (months):	24		

SURFACE PREPARATION AND PAINT SYSTEM

Remove any loose and peeling old paint or whitewash layers. Sandpaper the entire surface to smooth it. Clean surface from all dust. Thoroughly mix the paint. Apply the first coat with the paint diluted with 20 % to 30 % of water. Apply second and third layers, as required, with the paint diluted with 15 % to 20 % of water. Allow 1 to 3 hours drying time between successive layers, in accordance with the weather conditions.

Application Remarks:

Polisid can be applied by using air - less spraying. This application method enables application rate to cover 350 Sq. Meters, in two layers, in merely 2 hours.

Do not apply the paint when outside temperature drops below + 10°C

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.