

Acrylic 609

Acrylic water-based paint for interior walls.

Qualities:

Light and easy to use, dries quickly, "breathes", with high coverage and whiteness, lead-free and chromate-free.

Uses:

For interior painting of ceilings and plaster, concrete and brick walls.

Technical Data:

Product code:	720-150		
Color:	White		
Gloss:	Matte		
Calculated spreading rate*:	6 sq m / liter (two coats)		
Dilution: during painting:	Water		
For cleaning:	Soap and water		
Drying times:	Touch dry**:	1 hour	Hard drying: 24 hours Dry to recoat: 3 hours
Shelf life:	24 months		
Quantity per surface:	Package size	Quantity per surface	
	16 liter	27	

Preparation of area and paint system:

Internal whitewashed areas:

Remove all free, loose, peeling lime wash and very thick layers. Sandpaper until a smooth surface is achieved. Remove all dust. Apply one coat of **Bonderol Super** and wait for it to dry fully. Apply 2-3 coats of **Acrylic 609**.

Interior walls covered with plastic paint:

Remove all old, loose and peeling paint and repair imperfections with **Calcimo X**. Smooth the surface with sandpaper. Apply 2-3 layers of **Acrylic 609**. If the previous coat is normal and cannot be removed, apply 2-3 coats of **Acrylic 609** directly over it.

New unpainted interior walls (plaster):

Lightly sandpaper surface. Remove all dust and fill holes with **Calcimo X**. To achieve a smooth surface, apply **Magic Bond** or a coat of **Tambourfill** and wait until fully dry. Apply 2-3 coats of **Acrylic 609**.

Painting:

Stir the paint well prior to use and from time to time during painting.

Painting with a brush/roller/airless: Dilute the paint for the first coat with 15-20% water and mix well. Dilute the paint for the additional coats with 10-15% water. Apply 2-3 coats depending on surface type.

Tool cleaning and storage:

Clean tools with soap and water immediately upon completion of the work. Pour a thin layer of water onto the remaining paint and close the packaging well to prevent air from penetrating. Store in a dark, well-ventilated area.

Safety warnings and instructions:

The paint is non-edible. It is not defined as a hazardous material and does not contain substances requiring special markings or warnings. Keep away from the reach of children. Ensure proper ventilation during painting. Detailed information on the product may be found on the Manufacturer's Safety Data Sheet (MSDS).

General Comments:

Do not paint when rain is about to fall and/or the temperature is below 10°C and relative humidity above 85%. This material must not be mixed with materials not recommended by the manufacturer.

Achieving the best results depends on the proper application of the product and on the strict compliance with our instructions. Before application, the user should verify that the product is designed for the intended usage and that the surfaces to be painted are properly prepared and suitable for the product's application.

The data presented herein are based on the knowledge and experience acquired over many years. We reserve the right to update and/or alter the data without prior notice.

* Practical spreading rate depends on several factors: surface area, manner of painting, painting color, painter's expertise, and on-site weather conditions. The accepted assumption is that it constitutes approx. 75% of the calculated spreading rate.

** At 25° C and 65% relative humidity.

Manufactured by Tambour, certified by the Israeli Standards Institute in accordance with ISO 9001.