

# PLASTIKIR

## Plastic, Water Based Paint for Interior Walls

### SPECIAL FEATURES

Good adhesion to the substrate, breathing, lead and chromates free.

### SUGGESTED USES

Painting interior plaster, concrete and brick walls.

### TECHNICAL DATA

Product code: 731-800  
 Color: White  
 Gloss: Matt  
 Calculated spreading rate\*: 5-6 sq.m/liter (in two coats)  
 Recommended Thinner: **During application:** water. **For cleaning:** water and soap.  
 Drying Times: **Touch dry\*\*:** 1 hour. **Hard coat:** 3 hours **Dry to recoat:** 3 hours  
 Shelf life: 24 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
5 liters	125
18 liters	27

### SURFACE PREPARATION AND PAINT SYSTEM

#### Interior Whitewashed surfaces

Remove any flakey, loose or peeling lime and excessively thick coats. Sand with sandpaper until a smooth surface is obtained. Clean dust thoroughly. Fill holes with **Calcimo X** if needed. Apply one coat of **Bonderol Super Primer** and allow drying to a hard coat. Apply two coats of **Plastikir**.

#### Painted Interior Walls

Remove any flakey, loose or peeling old paint. Apply a coat of **Bonderol Super Primer** in peeling paint sections. Smooth the surface with **Joint Compound** or **Glue Putty 2000** and apply a coat of **Bonderol Super Primer** over it. Allow to dry and apply two coats of **Plastikir**. When the old paint is intact and cannot be removed, apply 2 coats of **Plastikir** directly on that paint.

#### New Interior Unpainted Walls

Smooth the surface lightly with sandpaper. Remove dust and fill holes with **Calcimo X**. Apply a coat of **Tambourfill** diluted with water by 20%-30% and allow drying to a hard coat. Apply two coats of **Plastikir**.

### APPLICATION REMARKS

Stir the paint well before painting and during application **Brush/ Roller/ Airless spray application:** For the first coat, dilute with water by 15%-20% and stir well. For additional coats, dilute with water by 10%-15%. Apply 2-3 coats, according to the surface type.

### CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

### CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

### GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.