

# GOLD PAINT

## Decorative Gold paint for wood and metal

### SPECIAL FEATURES

This paint is not durable in chemical, acidic or alkaline environments.

### SUGGESTED USES

For interior and exterior application on metal surfaces.

### TECHNICAL DATA

Product code:	605-001	
Color:	Gold	
Gloss:	Metallic	
Calculated spreading rate*:	10 sq.m/liter (in one coat)	
Recommended Thinner:	<b>During application:</b> Tambour Mineral White Spirit or Thinner 1-32. <b>For cleaning:</b> Tambour Mineral White Spirit or Thinner 1-32.	
Drying Times:	<b>Touch dry**:</b> 1 hour. <b>Hard coat:</b> 24 hours <b>Dry to recoat:</b> 16 hours	
Shelf life:	24 months	
Quantity per Pallet:		
	<b>Package size</b>	<b>Quantity per Pallet</b>
	0.25 liter	1440
	0.75 liter	576

### SURFACE PREPARATION AND PAINT SYSTEM

#### All Types of Metal

Prior to application, ascertain that the surface is clean and dry: Remove any grease, dirt, rust, metal scales and any other foreign matter, using a steel brush or sandpaper. Proceed to rinse with Tambour Mineral White Spirit. Apply one coat of **Bazak Primer** and allow drying to a hard coat. Apply 2 coats of **Gold Paint**.

When it is impractical to remove rust mechanically or chemically, as indicated above, you can neutralize the rust by applying **Rust Converter**, followed by 1-2 coats of **Bazak Primer** and allow drying to a hard coat. Apply two coats of **Gold Paint**.

### APPLICATION REMARKS

Ready to use paint. Stir well before application and while painting. Recommended film thickness per coat is 50 microns (dry).

**Brush/ Roller Application:** Thin with Tambour Mineral White Spirit up to 5%, when needed.

**Regular Spray Application:** Thin with **Thinner 1-32** up to 5% and spray at a pressure of 4 atmospheres.

**Airless Spray Application:** Thin with **Thinner 1-32** up to 5% and spray at a pressure of 4 atmospheres, nozzle diameter 0.014".

### CLEANING AND STORAGE

Clean work tools with the thinner used during application immediately after use. Close the container tightly to prevent air penetration. Store in roofed and ventilated place.

### CAUTION

Inedible, keep away from fire, keep out of reach of children. Protect eyes and skin during application. Use in a well ventilated area only. Avoid inhaling the paint or its fumes. Wash your hands with water and soap after completing application. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

### GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

\* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

\*\* at 25°C and 65% relative humidity.