

# SILVER PAINT

## Excellent Aluminum Shade Paint for Metal

### SPECIAL FEATURES

Resists temperatures of up to 100°C. Excellent exterior durability. Does not resist chemicals, acids or alkali environments.

### SUGGESTED USES

Interior and exterior application on metallic surfaces.

### TECHNICAL DATA

Product code: 600-001  
 Color: Aluminum  
 Gloss: Metallic  
 Calculated spreading rate\*: 17 sq.m/liter (in one coat).  
 Recommended Thinner: **During application:** Brush: Tambour Mineral White Spirit, Roller: Thinner 1-32.  
**For cleaning:** Tambour Mineral White Spirit or Thinner 1-32.  
**Touch dry\*\*:** 1 hour **Hard coat:** 24 hours **Dry to recoat:** 16 hours  
 Drying Times:  
 Shelf life: 24 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
0.25 liter	1440
0.75 liter	900
4.5 liters	100

### SURFACE PREPARATION AND PAINT SYSTEM

Prior to application ascertain that the surface is clean and dry. Remove any grease, dirt and rust, metal flakes and any other foreign matter using a steel brush and sandpaper, then rinse with Tambour Mineral White Spirit. Apply a primer coat of **Bazak Primer** and allow drying to a hard coat. Apply two coats of **Silver Paint**. When it is impractical to remove rust mechanically or chemically, as indicated above, you can neutralize the rust by applying **Tambour Rust Converter**, followed by 1-2 coats of **Bazak Primer** and allow drying to a hard coat. Apply two coats of **Silver Paint**.

### APPLICATION REMARKS

Ready to use paint. Stir the paint well before application and while painting.  
**Brush/ Roller Application:** Thin up to 5% with Tambour Mineral White Spirit when needed.  
**Regular Spray Application:** Spray at a pressure of 4 atmospheres. Thin up to 5% with Thinner 1-32.  
**Airless Spray Application:** Spray using a gun with a 0.015" diameter nozzle at a pressure of 4 atmospheres. Thin up to 5% with Thinner 1-32.

### CLEANING AND STORAGE

Clean work tools with white spirit or Thinner 1-32 (according to the thinner used during application), immediately after use. Close the container tightly to prevent air penetration. Store in roofed and ventilated place.

### CAUTION

Inedible, flammable, keep away from fire. Keep out of reach of children. Protect skin and eyes during application. Use in a well ventilated area only. Avoid inhaling the paint or its fumes. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

## GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

\* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

\*\* at 25°C and 65% relative humidity.