

Supercryl More

A water-based acrylic paint with excellent coverage capabilities. Good for indoor and outdoor applications

Features:

Provides extremely high coverage and an attractive and highly durable appearance – does not peel or fade. Quick drying and breathing paint. Meets Israeli Standard 1945 for internal and external paints, has low VOC, and possesses Green Seal 1738.

Uses:

For internal and external painting of plaster, concrete and brick walls.

Technical Specifications:

Product Code:	White: 732-501	Pastel Base 732-502
Colour:	White and 400 pastel shades from Tambour Spectrum fan deck.	
Surface:	Matt	
Calculated Coating Ability*:	9-10 sq meters/liter (two coats)	
Recommended Thinner:	Water	Cleaning: Soap and Water
Setting Time:	Dry to Touch**: 1 hour	Hard Setting: 3 hours (7 days before rain). Dry to recoat: 2-3 hours
Shelf Life:	24 Months	
Quantity per Pallet:		
	Package Size	Quantity per Pallet:
	18 liters	27
	10 Liters	60

Surface and Paint System Preparation

Whitewashed Internal Areas:

Remove any free, loose or too-thick whitewash. Sand until smooth. Clean well of dust. Apply one coat of **Bonderol Super** and wait 4 hours until dry. Apply two coats.

Internal Walls Painted with Plastic Paints:

Remove old, loose or peeling paint. Apply **Bonderol Super** where paint is peeling. Smooth surface with **Magic Bond** or **Glue Putty 2000** (indoor use only), coat with **Bonderol Super** and wait until dry. Apply two coats of **Supercryl More**.

If the old paint is in good condition and cannot be removed, apply directly 2 coats of **Supercryl More**.

Unpainted new Internal Walls:

Gently sand the surface. Remove dust and fill holes with **Calismo X**. For a smooth surface apply coat of **Magic Bond** or **Tambourfill** and wait until fully dry. If **Magic Bond** is applied, a layer of **Bonderol Super** is necessary. Apply 2 coats of **Supercryl More**.

Concrete and Cement Plaster Surfaces:

Paint only after finishing (at least a month after application). Clean dust, and apply first coat of **Tambourflex Bonding Primer**, diluted with 30% mineral turpentine. After at least 24 hours, apply 2 coats of **Supercryl More**.

Application

Stir well before use and occasionally throughout application. Brush/roller/spray painting – dilute first layer of paint with 20%-30% water and mix well. Dilute paint of additional layers with 10%-20% water. Apply 2 coats according to surface.

Tool Cleaning and Storage

Clean work tools with water and soap immediately after finishing work. Pour thin layer of water on remaining paint and seal packaging against air. Store in covered and ventilated place.

Warnings and Safety Instructions:

The paint is not to be eaten; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Specific information regarding the product is available in the safety manual (MSDS).

General Notes:

Do not apply when rain is expected and/or the wall temperature is under 10°C and the relative humidity is over 85%. Do not mix this product with products not recommended by us. Achieving desired results is contingent upon following all instructions concerning the proper application of the product. Prior to applying the product, the user must make sure that application of the product is in the intended manner, and that the surface to be painted and its infrastructure have been properly prepared and appropriate to the product's application.

The information presented is based on knowledge and experience accumulated over the course of years. We reserve the right to update and/or change it at our discretion.

* The actual coverage is contingent on several factors: the surface, the manner of painting, the color, the painter's expertise and on-site weather conditions. The assumption is that it consists of 75% of the calculated coverage capability.

** At 25°C and 65% relative humidity.