

# ACRYLIC PAINT 809

## Water Based Acrylic Paint for Interior Walls

### SPECIAL FEATURES

Easy application. Fast drying. "Breathing". High spreading rate and whiteness. Free of lead and chromates. Conforms to the requirements of IS809

### SUGGESTED USES

Interior plaster, concrete and bricks walls and ceilings.

### TECHNICAL DATA

Product code: 700-501 White / 700-502 Pastel Base  
 Color: White + pastel shades.  
 Gloss: Matt  
 Calculated spreading rate\*: 6 sq.m/liter (in two coats)  
 Recommended Thinner: **During application:** water. **For cleaning:** water and soap.  
 Drying Times: **Touch dry\*\*:** 1 hour. **Dry to recoat:** 3 hours **Hard coat:** 24 hours  
 Shelf life: 24 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
18 liters	27

### SURFACE PREPARATION AND PAINT SYSTEM

#### Interior Whitewashed Walls:

Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Apply one coat of **Bonderol Super**. Allow to dry for 4 hours and apply two coats of **Acrylic Paint 809**.

#### Interior Walls Painted with Plastic Paint:

Remove any old, loose and peeling paint and repair defects with **CalcimoX**. Sand with sandpaper to a smooth surface. Apply 2-3 coats of **Acrylic Paint 809**. When the old paint coat is in good condition and cannot be removed, apply 2-3 coats of **Acrylic Paint 809** directly on it.

#### New, Unpainted, Plastered Interior Walls:

Smooth the surface lightly using sandpaper. Remove dust and fill holes with **Calcimo X**. To obtain a smooth surface, apply a coat of **Tambourfill** and allow drying for 4 hours. Apply 2-3 coats of **Acrylic Paint 809**.

### APPLICATION REMARKS

Stir the paint well before application and while painting.

#### Apply using a brush/ Roller/ Airless:

Dilute the paint with water for the first coat by 15% - 20% and stir well. Dilute the paint with water for the additional coats by 10%-15%. Apply 2-3 coats, according to the surface type.

### CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed, ventilated place.

### CAUTION

Inedible. This paint is not defined as a hazardous material and does not contain materials requiring special marks or warnings. Keep out of reach of children. Use in a well ventilated area only. Safety data sheets are detailed in the safety data sheet (MSDS).

## GENERAL COMMENTS

Do not apply the paint when rain is expected or when ambient temperature falls below 10 degrees Celsius and relative humidity exceeds 85%.

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

IS809 + abrading table, Green label, 7 years warranty.

Made by Tambour, certified by the Israeli Standards Institute, in conformance to ISO-9001

## Notes:

\* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 25% as a loss factor.

\*\* at 25°C and 65% relative humidity.